

FEATURES


- Unidirectional protection of one line
- Reverse standoff voltage: $V_{RWM} = 4.8\text{ V}$
- Average Surge current for 8/20 μs pulse: $I_{PPM} = 160\text{ A}$ (rated)
- Ultra low clamping voltage
 $V_{CL} = 15\text{ V typ. at } 160\text{ A}$

APPLICATIONS

- Portable electronics
- Power supply protection
- Power management



DFN1610




Marking

IEC COMPATIBILITY

- IEC61000-4-2 (ESD) $\pm 30\text{ kV}$ (air), $\pm 30\text{ kV}$ (contact)
- IEC61000-4-4 (EFT) 40A (5/50ns)

APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003



Schematic Symbol



THERMAL CONSIDERATIONS

Symbol	Parameter	Value	Unit
P_{pp}	Peak Pulse Power (tp=8/20 μs waveform)	1500	Watts
T_J	Operating Temperature Range	-55 to +125	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-55 to +125	$^{\circ}\text{C}$

ELECTRICAL CHARACTERISTICS


Symbol	Parameter	Condition	Min.	Typ.	Max.	Unit
V_{RWM}	Reverse Stand-off Voltage				4.85	V
V_{BR}	Reverse Breakdown Voltage	$I_T = 1\text{ mA}$	4.9		5.4	V
I_R	Reverse Leakage Current	$V_R = 4.5\text{ V}$			0.1	μA
I_R	Reverse Leakage Current	$V_R = 4.85\text{ V}$			0.2	μA
V_C	Clamping Voltage	$I_{PP} = 160\text{ A}, t_p = 8/20\mu\text{s}$			15	V
I_{PP}	Peak Pulse Current	$t_p = 8/20\mu\text{s}$			160	A
V_F	Forward Voltage	$I_F = 10\text{ mA}$			1.2	V
C_J	Off State Junction Capacitance	$V_R = 0\text{ V}, f = 1\text{ MHz}$ Level=50mV		650		pF

CHARACTERISTIC CURVES



SOLDERING PARAMETERS

Reflow Condition		Lead-free assembly
Pre Heat	Temperature Max ($T_{s(min)}$)	150°C
	Temperature Max ($T_{s(max)}$)	200°C
	Time (min to max) (t_s)	60 – 180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak)		3°C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	Temperature (T_L) (Liquidus)	217°C
	Time (min to max) (t_L)	60 – 150 seconds
Peak Temperature (T_p)		260°C
Time within 5°C of actual peak Temperature (t_p)		20 – 40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_p)		8 minutes max.
Do not exceed		260°C



Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.