



FEATURES

- | Super Fast Switching For High Efficiency
- | Low Reverse Leakage
- | High Forward Surge Current Capability

PRIMARY USE

- | Mainly Used In Switching Power Supply, PWM Pulse Width Modulator, inverter as A Freewheeling And Other Electronic Circuits, High-Frequency Rectifier Diode, Diode or Damping Diode use



APPROVALS

RoHS	Compliance with 2011/65/EU
HF	Compliance with IEC61249-2-21:2003

MAXIMUM RATINGS ($T_A=25^{\circ}\text{C}$)

Parameter	Symbol	Value	Unit
Maximal Inverted Repetitive Peak Voltage	V_{RRM}	400	V
Average Rectified Forward Current (Rated VR-20Khz Square Wave) - 50% duty cycle	I_{FAV}	60	A
Max.forward Surge Current ,8.3ms Single Half Sine-Wave Superimposed On Rated Load	I_{FSM}	340×2	A
Operating Junction Temperature	T_J	-40 to 175	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-40 to 175	$^{\circ}\text{C}$
Typical Thermal Resistance(per leg) Package=TO-247	$R_{\theta JC}$	0.5	$^{\circ}\text{C/W}$

ELECTRICAL CHARACTERISTICS($T_A=25^{\circ}\text{C}$)

Item	Test Conditions		Min.	Typ.	Max.	Unit
V_B	$I_R=100\mu\text{A}, T_J=25^{\circ}\text{C}$		400			V
I_R	$V_R=400\text{V}, T_J=25^{\circ}\text{C}$				0.01	mA
	$V_R=400\text{V}, T_J=125^{\circ}\text{C}$				0.10	
V_F	$I_F=30\text{A}$ ($I_{FAV}=30\text{A} \times 2$)	$T_J=25^{\circ}\text{C}$		1.2	1.4	V
		$T_J=125^{\circ}\text{C}$			1.2	V
T_{RR}	$I_F=0.5\text{A}, I_R=1.0\text{A}, I_{REC}=0.25\text{A}$				50	nS

CHARACTERISTIC CURVES

Fig1: The Forward Voltage And Forward Current Curve




Fig2: Current Derating Curve, Per Element






FIG3: The Reverse Leak Current And The Reverse Voltage (Single-Device) Curve.




WAVE SOLDERING



Wave Parameter		Lead-free assembly
Pre Heat	Temperature Min	100°C
	Temperature Max	150°C
	Time(min to max)	60 – 180 secs
Solder pot Temperature		280°C Max
Solder Dwell Time		2-5 seconds

TO-247 PACKAGE INFORMATION



Ref.	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	15.4	15.8	0.606	0.662
B	19.5	20.5	0.767	0.807
C	1.8	2.2	0.070	0.087
D	1.15	1.25	0.045	0.050
E	5.2	5.7	0.204	0.225
F	2.8	3.2	0.110	0.126
G	3.4	3.8	0.133	0.149
H	4.8	5.2	0.188	0.205
I	14.0	14.5	0.550	0.570
J	0.4	0.7	0.015	0.029
K	2.4		0.095	

ORDERING INFORMATION

Part Number	Component Package	Marking	QTY/Tube	QTY/Box	QTY/Carton
SFP6004	TO-247	SFP6004	30PCS	450PCS	2250PCS

Headquarters

No.3387 Shendu Road
Pujiang I&E Park
Minhang Shanghai China
201000

Hotline

400-021-5756

Web

<https://www.semiware.com>

Sales Center

Tel: 86-21-3463-7458
Email: sales18@semiware.com

Customer Service

Tel: 86-21-5484-1001
Email: sales17@semiware.com

Technical Support

Tel: 86-21-3463-7654
Email: fae01@semiware.com

Complaint & Suggestions

Tel: 86-21-3463-7172
Ext: 8868
Email: cs03@semiware.com

By QR Code

Website



Wechat

To find your local partner within Semiware's global website: www.semiware.com

© 2022 Semiware Semiconductor Inc.

The content of this document has been carefully checked and understood. However, neither Semiware nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Semiware does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Chinese law and resulting disputes shall be settled by the courts at the place of business of Semiware. Latest publications and a complete disclaimer can be downloaded from the Semiware website. All trademarks recognized.